



TEAFLEX[®] M

www.teaflex.com

EXPRAT**Pressacavi anti torsione in ottone nichelato**
Strain relief cable glands nickel plated**DIAMETRO GANASCE SERRATE**
CROSS SECTION LOCKED JAWS**Certificazioni / Approvals:**
EN 62444
CE
RINA
Grado di protezione: IP 68
IP Rating: IP 68**Applicazione**
Application

Le particolari ganasce di questi pressacavi oltre a garantire un'eccezionale tenuta a trazione del cavo evitano la possibilità di torsione del cavo stesso.
Pressacavi in ottone nichelato con gommino di serraggio in TPE e anello "O" ring sulla filettatura. **Viti di serraggio acciaio inox AISI 304.**

Note: I gommini sono facilmente riconoscibili grazie al codice articolo stampato sul prodotto.
Colore: blu RAL 5005

The particular design of the jaws guarantees an excellent strain relief of the cable avoiding jerking movements.
*Strain relief brass cable glands nickel plated with TPE insert and "O" ring on thread. **Stainless steel AISI 304 locking screws.***

Remarks: Sealing inserts are easily recognizable thanks to the Part n. printed on the product.
Color: blue RAL 5005.

**RINA****EXPRAT - Pressacavi industriali antitorsione in ottone nichelato**

CODICE GAS	F Filetto GAS	A mm	OD1-OD2 mm	SP1-SP2 mm	CODICE PG	F Filetto PG	A mm	OD1-OD2 mm	SP1-SP2 mm	CODICE ISO METRICO	F Filetto ISO Metr.	A mm	OD1 OD2 mm	SP1 SP2 mm	Certificazioni	B mm	Ø cavo mm min. max.	Codice gommino	Confez. Standard KIT				
EXPRAT01211	1/2"	9	26-27	24	EXPRAT1311	13,5	6,5	24-27	22-24	EXPRATM2011	M20x1,5	8	24-27	22-24	  	9,1	7 - 10,5	GPR01311	50				
EXPRAT01213					EXPRAT1313					EXPRATM2013							9 - 13	GPR01313					
EXPRAT03413	3/4"	10	30,5-29	28-26	EXPRAT1613	16	6,5	26,5-29	24-26	EXPRATM2513	M25x1,5	9	30-29	28-26	  	10,5	9 - 13	GPR01613	50				
EXPRAT03416					EXPRAT1616					EXPRATM2516							11,5 - 15,5	GPR01616					
EXPRAT03418			32-33	30												EXPRATM2518	33-29	30-26	  	13,1	14 - 18	GPR02118	20
EXPRAT03420																					EXPRATM2520	17 - 20,5	
EXPRAT10016	1"	11	38,5-33	35-30	EXPRAT2116	21	7,5	32-33	30	EXPRATM3216	M32x1,5	10	37,5-33	35-30	  	13,1	11,5 - 15,5	GPR02116	20				
EXPRAT10018					EXPRAT2118					EXPRATM3218							14 - 18	GPR02118					
EXPRAT10020			43-44,5	40											EXPRATM3220	43-44,5	40	  		19,5	17 - 20,5	GPR02120	
EXPRAT10025																					EXPRAT2920	EXPRATM3225	20 - 25
					EXPRAT2920	29	9,25	43-44,5	40	EXPRATM4020	M40x1,5	10	47-44,5	42-40	  	19,5	17 - 20,5	GPR02920	15				
				EXPRAT2925	EXPRATM4025					20 - 25							GPR02925						
				EXPRAT2928	EXPRATM4028					24 - 28							GPR02928						
EXPRAT11430	1"1/4	9	48-50	45						EXPRATM4030								10	48-50	45	  	21,5	26 - 30
EXPRAT11232	1"1/2	9	55-56	50	EXPRAT3632	36	9	55-56	50	EXPRATM5032	M50x1,5	10	57-56	52-50	  	24	27 - 32	GPR03632	10				
EXPRAT11234					EXPRAT3634					EXPRATM5034							29 - 34	GPR03634					
EXPRAT11236					EXPRAT3636					EXPRATM5036							32 - 36	GPR03636					
EXPRAT20044	2"	10	70	64	EXPRAT4844	48	10	70	64	EXPRATM6344	M63x1,5	10	70	64	  	39,5	39 - 44	GPR04844	5				
GAS KIT NUMBER	F GAS thread	A mm	OD1-OD2 mm	SP1-SP2 mm	PG KIT NUMBER	F PG thread	A mm	OD1-OD2 mm	SP1-SP2 mm	ISO METRIC KIT NUMBER	F ISO Metric thread	A mm	OD1-OD2 mm	SP1-SP2 mm	Certifications	B mm	Cable Ø mm Min. Máx.	Seal REF. Part N.	KIT Packing Unit				

EXPRAT - Industrial strain relief cable glands made of brass nickel platedEsempio d'ordine **KIT / KIT** Order example: **EXPRATM2516****EXPRAT** Pressacavo anti torsione in ottone nichelato - *Strain relief cable gland brass nickel plated***M** Filettatura ISO metrico - *ISO metric thread***25** Dimensione Filetto - *Thread dimension***16** Passaggio cavo 11,5-15,5 / *Cable range 11,5-15,5*