

**Applicazione**  
**Application**



I giunti a innesto rapido in metallo PC, permettono il collegamento tra i tubi rigidi metallici della serie STD e le guaine corrugate riducendo i tempi di installazione con risultato economico e sicuro.

L'ancoraggio ai tubi STD è garantito dal sistema AR già impiegato con successo nel corso degli anni da Teaflex. Soddisfano i requisiti standard nelle installazioni elettriche industriali e nelle applicazioni tecniche ad elevate prestazioni nell'industria pesante e nel settore ferroviario.

**Temperatura d'esercizio:** -40°C +105°C  
**Per breve periodo:** +150°C

Splice connectors with metal fittings type PC provide practical, economic and secure connections with STD zinc plated pipes, reducing time of installation.

The connection to STD pipes is long time successfully guaranteed by the AR system applied by Teaflex. Suit to standard requirements in industrial and electro technical installation applications as well as for increased requirements in heavy industry and railway applications.

**Temperature Range:** -40°C +105°C  
**Short term:** +150°C

**Certificazioni**  
**Approvals**



EN 61386 - 23 - EN 60529 IP68

CE

RINA

UL1696 - RU file E - 124066 - CURUS

ISO 20653 IP69K

EN 45545-2 (HL3 per l'esterno / set di requisiti R23)

EN 45545-2 (HL2 per l'interno / set di requisiti R22)

NFPA130:2020

PN-K-02511:2000

EN 61386 - 23 - EN 60529 IP68

CE

RINA

UL1696 - RU file E - 124066 - CURUS

ISO 20653 IP69K

EN 45545-2 (HL3 for external parts / requirement set R23)

EN 45545-2 (HL2 for internal parts / requirement set R22)

NFPA130:2020

PN-K-02511:2000

**Giunto a innesto rapido in METALLO per tubi STD e guaine corrugate**

Codice IP68-IP69K	Codice Guaina NW	Diametro metrico guaina	A Tubo STD mm	B mm	L mm	OD1 mm	OD2 mm	OD3 mm	Confezione standard
8BPC1216	12	16	16	14	60,65	24	27	24	50
8BPC1720	17	20	20	18	61,85	30	31	28	50
8BPC2325	23	25	25	22,5	72	38	36	33	30
8BPC2932	29	32	32	29,5	72,5	45,5	44	40	20
8BPC3640	36	40	40	37,5	86	57	55	50	20
8BPC4850	48	50	50	47,5	92,5	68	65	60	10
Type IP68-IP69K	Conduit Code NW	Fits to metric Conduit	A Fits to STD Pipe mm	B mm	L mm	OD1 mm	OD2 mm	OD2 mm	Packing unit

**Connection splice with METAL fitting between STD pipes and corrugated conduits**

Esempio d'ordine / Order example: **8BPC2932**


**8** Grado di protezione: IP69K-IP68 statico / IP67 dinamico  
IP Rating: IP69K-IP68 static / IP67 dynamic

**B** Colore - Colour

**PC** Codice serie - Family type

**29** Diametro nominale guaina - Nominal width

**32** Diametro tubo STD - STD pipe nominal width



QR CODE: istruzioni di  
montaggio  
QR CODE: assembly  
instructions